



AQUA CLEAR
Water Systems

NRO 440 SERIES SYSTEMS

1.1 - 6.9 Gallons per Minute

NRO

Commercial Reverse Osmosis

The **NRO Commercial Series of Reverse Osmosis Systems** are custom built to your specifications. These commercial systems of unmatched value in quality and price give you a multitude of standard features that are optional on most other ROs!

NSF-grade high quality parts are used to build this tough system. All **Commercial Systems** are wet tested to optimum pressure and production prior to shipment.

The **NRO 440 Series** is designed for Commercial or Light Industrial applications requiring flow rates of 1.1-6.9 gallons per minute (GPM). The **NRO 440 Series** features the durability of a powder coated steel frame, an optional complete performance monitoring package, and simple system integration.



*Easy Motor
Mount Bracket*




*Stainless Steel Multi
Stage Booster Pumps*



*Permeate & Concentrate
Flow Meters*



*Optional - Control Box w/Low
Pressure, Permeate TDS
& Level Controls*



*Gloss 300 psi FRP
Membrane Housings, Stainless
Steel Also Available*



*Liquid Filled Panel
Mounted Concentrate
Pressure Gauge*



SYSTEM FEATURES & OPTIONS

System Features Include:

- **Carbon Steel Frame** for strength & rigidity
- **Powder Coated Frame** for long life & durability
- **Extended Frame Legs** with plastic end caps for protection from ground contact and ease of movement
- **Replaceable Motor Mounting System** - makes field repairs easy, bracket mounts to motor and slides over frame
- **True Union Couplings** on inlet & outlet of motor
No plumbing disassembly required for change out
- **Stainless Braided Hoses** for protection against corrosion, leaks & fraying
- **Replaceable Schedule 80 PVC** fittings for ease of field repairs
- **Quick Connect Fittings** on gauges & recycle operation for ease of service
- **Brass or Stainless Steel** inlet shut off valve
- **High Flow TFC Low Pressure Membranes** - additional element types & ratings available
- **High Quality Gloss 300 psi FRP Housings** - *stainless housings available at no additional cost*
- **Integrated Recycle Valve**
- **Low Pressure Mechanical Switch** w/time delay snubber valve
- **Permeate & Concentrate Flow Meters**
- **Liquid Filled Gauges** for accurate & steady pressure readings
- **Panel Mounted Concentrate Pressure Gauge**
- **Stainless Steel High Pressure Centrifugal Pump** for lasting performance
- **Pump Throttle Valve** & pipe mounted discharge pressure gauge
- **Float Switch & Pretreatment Interlocks** - standard on all systems
- **High Flow 5 Micron** front mounted prefilter for ease of service

Optional NRO Series Upgrades:

- **Digital Display Electronic Control Box** with permeate TDS display, low pressure auto reset
- **Private Labeling Available**
- **Custom Photo Quality Controller Graphics** available (min order quantity required)
- **Upgrade Control Box** for interval fast flush
- **Upgrade Control Box** for permeate flush
- **Custom Operational Programs** at no cost
- **Second TDS Function** for feed water
- **Additional Panel Mounted Gauges** - customer specified
- **Pre & Post Filter Gauges**
- **Manual Auto Flush Valve**
- **Interstage Gauges**
- **Bladder Tank Control** available to provide pressurized storage
- **Wall Mount Frame**



Aqua Clear has many years of technical experience and service expertise ready to help optimize the performance of your system or build a system to your specific needs!

Commercial Reverse Osmosis System Specifications

Model:	NRO-F-1440F-1600-3	NRO-F-2440F-3200-3	NRO-F-3440F-4800-3	NRO-F-4440F-6400-3	NRO-F-5440F-8000-2	NRO-F-6440F-10000-2
Production GPD****	1600	3200	4800	6400	8000	10,000
Membrane	4 X 40 (1)	4 X 40 (2)	4 X 40 (3)	4 X 40 (4)	4 X 40 (5)	4 X 40 (6)
Permeate GPM	1.11	2.2	3.3	4.5	5.7	6.9
Feed GPM*	6.0	7.0	8.0	9.0	10.0	11.0
% Recovery w/Recycle	19%-30%	50%-75%	50%-75%	50%-75%	50%-75%	50%-75%
Pump	1 HP	1 HP	1.5 HP	1.5 HP	3 HP	3 HP
FLA 60HZ 1Ø 220	19.2/9.6	19.2/9.6	*12	*12	*15	*15
Circuit Size	20/15A	20/15A	15A	15A	20A	20A
Inlet	3/4"	3/4"	3/4"	3/4"	1" Big Blue®	1" Big Blue®
Permeate	1/2"	1/2"	1/2"	1/2"	1"	1"
Concentrate	1/2"	1/2"	1/2"	1/2"	1"	1"
Shipping Dims	34"x34½"x58½"	34"x34½"x58½"	34"x34½"x58½"	34"x34½"x58½"	34"x34½"x58½"	34"x34½"x58½"
Weight - Pounds	124 lbs.	149 lbs.	158 lbs.	169 lbs.	211 lbs.	224 lbs.
Max Operating Pressure	160 psi	160 psi	160 psi	160 psi	160 psi	160 psi



AQUA CLEAR
Water Systems

865-986-4234

* 110 Volt Not Available ** Consult Factory *** Minimum pressure of 35psi dynamic
**** The stated product performance is based on data taken after 30 minutes of operation at the following test conditions: 2,000 mg/L NaCl solution at 225 psig (1.5 MPa) applied pressure, 15% recovery, 77° F (25° C), pH 6.5-7.0