
PRODUCT DATA SHEET



AIR INDUCTION IRON CONTROL SYSTEMS

SMARTCHOICE² GEN II AIR INDUCTION FILTERS SINGLE STAGE

The AIF II Iron Filtration system is a chemical free process to effectively manage Iron in well water systems. Air induction provides a source of oxygen that fuels oxidation and enhances the media's ability to filter the water.

Standard Features:

Exclusive Factory Exchange Program

Exclusive Media Exchange Module

SmartChoice™ GenII - "Total Water Management" Valve

Multi Color Backlit Display
Differentiates Between Softener and Filter

Red Screen Display to Alert User of Attention Needed

Screen Can Display Dealer Name and Phone Number

1" High Flow Design

Corrosion Resistant Components

No Fasteners, Screws, or Bolts

Single Motor Driven Piston Operated

Lifetime Seamless Fiberglass Wrapped Resin Tank

1" MIP Pipe Connections w/ 1" Internal Check Valve on Inlet

Optional Features:

Rain Cover For Outdoor Installations pH Ajustment Module

Operating Conditions:

- pH ≥ 7.0 if < 7.0, pH Must Be Adjusted
- · Outside Water Usage Must Be Bypassed
- · No Chlorine, or Other Chemicals, in Feed Water
- Secure Drain Connection Code Compliant

PRODUCT SPECIFICATIONS

Model	Tank	Cont FR	Iron	Pipe	Max Drain	Drain	Dist
No.	Size	15 psi Drop	Reduction	Conn. Size	Flow gpm	Size	Туре
AIFII1054SIF	10" x 54"	8 gpm	.1 - 7 ppm	3/4" - 1"	3.2	5/8"	Vortech
AIFII1354SIF	13" x 54"	10 gpm	.1 - 7 ppm	3/4" - 1"	4.2	5/8"	Vortech

ADDITIONAL OPERATING INFORMATION

Not intended to be used to treat water that is Microbioloically unsafe or of unknown quality without adequate disinfection before or after the system. Installation must comply with all state and local codes.

Operating Water Temperature Range Operating Ambient Temperature Range Operating Pressure Range Electrical components Max 100° Max 120° Max 125 psi 110v - 60 hz 0.5 Amperes Minimum 40° Minimum 40° Minimum 20 psi

See manufacturer's warranty sheet for details on warranty

Parts or Service

