

Kinetico  
**PREMIER**  
SERIES®

WATER SOFTENERS

**PERFORMANCE DATA SHEET**  
Water Softening Systems



**Model/Product Numbers**

2030s (11020A)

2040s OD (11120)

2050s (11112)

2050c (12503A)

2060s (11006)

4040s OD w/Chloraban™ (16515)†

4060s OD w/Carbon (11215)†

4060s OD w/Macrolite® RX (11223)†

2060s OD (11201)

2100s (11032)

2175s (11036)

4040s OD (11057)

4050s (11092)

The Kinetico Premier Series® Water Softening Systems are tested and certified by the Water Quality Association (WQA) against NSF/ANSI Standard 44 for softener performance and reduction of barium and radium. In addition, the materials and components used in the construction of these systems have been tested to assure that levels of extractable contaminants do not exceed established limits set by NSF/ANSI Standard 44. They have also been evaluated under Standard 44 to assure that they are designed and constructed so their intended purpose can be accomplished when installed and operated in accordance with the manufacturer's instructions.

### **IMPORTANT**

- Installation of this product must comply with state and local plumbing laws.
- Provisions for an antisiphon air gap should be part of the installation to prevent a cross connection between the water system and the waste system.
- Waste connections or drain outlets shall be designed and constructed to provide for connection to the sanitary water system through an air gap of 2 pipe diameters or 1 inch (25mm) whichever is larger.
- Do not use on water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system, or that contains high concentrations of sediment, dirt or other suspended matter without additional treatment steps.
- Read this performance data sheet and compare the capabilities of this unit with your actual water treatment needs.
- It is recommended that before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs.
- The reduction of barium and radium 226/228 is directly related to the softening performance of your system. Have your system tested for hardness reduction every few months to assure the system is softening properly. Please note that barium and radium are not necessarily in your water supply.
- For operation and maintenance information, consult the product owner's manual. Installation instructions are available for review from your authorized Kinetico Dealer.
- Kinetico recommends the use of a quality grade pure salt (sodium chloride) processed especially for water conditioners.
- Water conditioners using sodium chloride for regeneration add sodium to the water. Persons who are on sodium restricted diets should consider the added sodium as part of their overall sodium intake.
- An efficiency rated water softener is a DIR softener which also complies with specific performance specifications intended to minimize the amount of regenerant brine and water used in its operation. These softeners shall have a rated salt efficiency of not less than 3350 grains of total hardness exchanged per pound (477 grams per kilogram) of salt (based on NaCl equivalency) and shall not deliver more salt than its listed rating. The efficiency is valid only at the low salt dosage and is measured by a laboratory test described in NSF/ANSI Standard 44. The test represents the maximum possible efficiency that the system can achieve. Operational efficiency is the actual efficiency achieved after the system has been installed. It is typically less than the efficiency due to individual application factors including water hardness, water usage, and other contaminants that reduce the softener's capacity.

### **WARRANTY COVERAGE**

Kinetico Incorporated warrants this product to be free from defects in material and workmanship for a period of ten years from the date of installation (freight and labor charges not included). For a period of ten years from installation date, faulty resin/media tanks and salt storage tank will be replaced at no charge. A formal copy of the Warranty for Residential Applications is presented at the time of purchase. Please contact your local authorized Kinetico Dealer with any questions about the warranty, parts or service.

### **CONTAMINANT REDUCTION CAPABILITIES**

**IMPORTANT NOTICE!** Read this performance data sheet and compare the capabilities of this unit with your actual water treatment needs. It is recommended that before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs. Please note that barium and radium are not necessarily in your water and that while testing was performed under standard laboratory conditions, actual performance may vary. The system has been tested according to NSF/ANSI Standard 44 for reduction of barium and radium 226/228. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 44. The charts on the following pages list the specifications and reduction capabilities by model and contain the following information based on WQA test results:

- The percent of reduction that can be expected
- Conditions under which the units were tested (pressure, pH and temperature)
- Influent and effluent levels of contaminated tested water
- The USEPA's maximum contaminant level (MCL)

**SPECIFICATIONS:**

**Minimum/Maximum Operating Pressure:** 103.4-861.9 kPa (15-125 psi)  
172.3-861.9 kPa (25-125 psi) for 2175s

**Maximum Working Pressure:** 861.9 kPa (125 psi)

**Minimum/Maximum Operating Temperature:** 2°C-49°C (35°F-120°F)


MODEL	2030s			2060s		2060s OD	
Service flow rate at 15 psi (or less) drop gpm	9 (34.1 L/min)			11.5 (43.5 L/min)		23 (87.0 L/min)	
Resin per tank, cu. ft.	0.47			0.7		0.7	
Capacity per cycle, grains	6686	8591	9307	10837	14686	10837	14686
Grains exchanged per pound of salt	4457*	3580	3102	4515*	3338	4515*	3338
Salt used per cycle, lbs.	1.5	2.4	3.0	2.4	4.4	2.4	4.4
Max flow rate to drain during regeneration, gpm	1.6 (6.0 L/min)			2.1 (7.9 L/min)		2.1 (7.9 L/min)	

MODEL	2100s			2175s		2050s / 2050c			2040s OD		
Service flow rate at 15 psi (or less) drop gpm	11.5 (43.5 L/min)			12.7 (48.0 L/min)		7 (26.5 L/min)			11 (41.6 L/min)		
Resin per tank, cu. ft.	1.6			2.25		0.4			0.4		
Capacity per cycle, grains	23951	38722	48413	53791	60371	4315	4979	5714	4315	4979	5714
Grains exchanged per pound of salt	4264*	3872	3227	4303*	4025*	5393*	4979*	4571*	5393*	4979*	4571*
Salt used per cycle, lbs.	5.5	10.0	15.0	12.5	15.0	0.8	1.0	1.25	0.8	1.0	1.25
Max flow rate to drain during regeneration, gpm	3.5 (13.2 L/min)			5.4 (20.4 L/min)		1.6 (6.0 L/min)			1.6 (6.0 L/min)		

MODEL	4050s			4040s OD†			4060s OD w/Carbon**†		4060s OD w/Macrolite® RX***	
Service flow rate at 15 psi (or less) drop gpm	6 (22.7 L/min)			11 (41.6 L/min)			11 (41.6 L/min)		11 (41.6 L/min)	
Resin per tank, cu. ft.	Upper 0.4 resin	Lower 0.4 carb		Upper 0.4 resin	Lower 0.4 carb		Upper 0.25 carb	Lower 0.7 resin	Upper 0.2 macrolite	Lower 0.7 resin
Capacity per cycle, grains	4315	4979	5714	4315	4979	5714	13,715		14,883	
Grains exchanged per pound of salt	5393*	4979*	4571*	5393*	4979*	4571*	3,429		3,383	
Salt used per cycle, lbs.	0.8	1.0	1.25	0.8	1.0	1.25	4.0		4.4	
Max flow rate to drain during regeneration, gpm	1.6 (6.0 L/min)			1.6 (6.0 L/min)			3.0 (11.4 L/min)		2.5 (9.5 L/min)	

\* Meets California requirements of 4000 grains exchanged per pound of salt used. Efficiency is only certified at the low salt dosage and was determined in accordance with NSF/ANSI Std. 44.

\*\* Two (2) Tanks



Kinetico Premier Series Water Softening Systems are tested and certified by WQA against the requirements of NSF/ANSI Standard 44 for softener performance and chemical reduction of barium and radium 226/228. They are also certified to NSF/ANSI 372, Drinking Water System - Lead Content and the CSA Standard B483.1 - Drinking Water Treatment Systems.

†Kinetico Premier Series® 4040s OD w/Chloraban™, 4060s OD w/Activated Carbon, 4060s OD w/Macrolite® RX are not certified with WQA.

### Contaminant Reduction Capability

Read this performance data sheet and compare the capabilities of this unit with your actual water treatment needs. Please note that barium and radium are not necessarily in your water. It is recommended that, before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs. These charts contain information based on test results for the reduction of barium and radium 226/228. Hardness is used in the test water to verify this reduction.

2030s	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	4.5 gpm	4.5 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

2175s	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	8.6 gpm	8.6 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

2060s / 2060s OD	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	5.8 gpm/10 gpm	5.8 gpm/10 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

2050s / 2050c / 2040s OD	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	3.5 gpm/5.5 gpm	3.5 gpm/5.5 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

2100s	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	6 gpm	6 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

4050s / 4040s OD†	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	2.8 gpm/5.5 gpm	2.8 gpm/5.5 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

4060s OD w/Carbon† 4060s OD w/Macrolite†	Barium	Radium
Test Pressure	35 psi ± 5 psi	35 psi ± 5 psi
Test Flow Rate	5.5 gpm/5 gpm	5.5 gpm/5 gpm
pH	7.5 ± .5	7.5 ± .5
Influent Level	<10mg/L ± 10%	<25 pCi/L ± 10%
Effluent Level	<2.0	<5pCi/L
Percent Reduction	≥80	≥80
EPA Max. Allowable Product Water Level	2.0mg/L	5 pCi/L

Kinetico Premier Series® Water Softening Systems will reduce the levels of certain substances in drinking water. These substances are not necessarily in your water. Because we make these claims, the attached information was compiled to help you better understand how these products will perform in your home.

Please sign below to verify that you've read and understand the attached information.

**DEALER COPY**

<b>CONSUMER</b>
_____ Signature
_____ Name (please print)
_____ Address
_____ City, State, Postal Code

<b>AUTHORIZED KINETICO DEALER REPRESENTATIVE</b>
_____ Signature
_____ Salesperson's Name (please print)
_____ Dealer's Name
_____ Dealer's Address
_____ City, State, Postal Code
_____ Dealer's Phone Number

Kinetico Premier Series® Water Softening Systems will reduce the levels of certain substances in drinking water. These substances are not necessarily in your water. Because we make these claims, the attached information was compiled to help you better understand how these products will perform in your home.

Please sign below to verify that you've read and understand the attached information.

**CONSUMER COPY**

<b>CONSUMER</b>
_____ Signature
_____ Name (please print)
_____ Address
_____ City, State, Postal Code

<b>AUTHORIZED KINETICO DEALER REPRESENTATIVE</b>
_____ Signature
_____ Salesperson's Name (please print)
_____ Dealer's Name
_____ Dealer's Address
_____ City, State, Postal Code
_____ Dealer's Phone Number