

SOFTENER PLUS IRON FILTRATION

Hardness, Iron, and Manganese

- Softens water and removes unwanted iron and manganese
- Hybrid regeneration for efficiency and improved water quality



- Softens water and removes up to 10 ppm of ferrous or ferric iron
- Metered regeneration for efficiency and improved water quality
- Quick-connect fittings (includes straight and 90 degree elbow connectors)
- Provides high-capacity flow for reliable access to high-quality water
- Customized to your individual needs, including household size and plumbing
- System-level certified by IAPMO R&T to NSF/ANSI Standard 44
- Made in an IAPMO-certified manufacturing plant



ANTIMICROBIAL
TECHNOLOGY



CONTROL VALVE



PRESSURE TANK



MADE IN
USA

COMPONENTS & SPECIFICATIONS



SOFTENER SYSTEM SPECIFICATIONS

BRITA PRO® SOFT + IRON PLATINUM SERIES 1"

Part Number	BPCFES100J	BPCFES150	BPCFES200
Salt Used - Per Regeneration (Lbs)	15	22	30
Regeneration Programming	Pre-Fill Brine	Pre-Fill Brine	Pre-Fill Brine
Grains Capacity	32,000	45,000	60,000
Resin Quantity (FT3)	1	1 1/2	2
Mineral Tank	10X54	12X52	13X54
Tank Jacket	YES	NO	NO
Media Loaded	YES	NO	NO
Brine Tank Size	16X33	16X33	16X40
Salt Storage Capacity	258	258	338
Service Flow Rate	13	14	16
Pipe Size (IN.)	1	1	1
Min-Max Pressure (psi)	20-100	20-100	20-100
Min-Max Temperature (°F)	35-100	35-100	35-100
Backwash GPM	1.7	1.7	1.7
Plumbing Connections	1 Inch Male NPT Eblow	1 Inch Male NPT Eblow	1 Inch Male NPT Eblow
Bypass	YES	YES	YES
Total Height (IN.)	61	59	61

- Factory-set pre-fill brine
- Programmable contractor contact screen
- Color specific displays
- Water drop flow indicator
- 62 days diagnostic information including; flow rates, gallons since regeneration, days since regeneration, total regenerations since start up, peak flow rates, and days till regeneration
- Stores system configuration and operation data in nonvolatile memory
- Valve internally ported in 1 inch
- Battery back-up with up to 8 hours of power carry-over
- Fully customizable programming including times and cycle order
- Easy contractor set-up, program time of day and hardness
- Treated water brine refill
- Days override feature: 1-28 days available
- Scrolling Text Display
- Service Call Reminder (not programmed from factory)
- Low Battery Warning
- External Accessory Operation
- Multiple Regenerations per day
- Service Technician "Step-Through" Regeneration
- Optional Air Release Cycle

SYSTEM DIMENSIONS

Models	A (Inches)	B (Inches)	C (Inches)
BPCFES100J	61"	10"	16.5"
BPCFES150	59"	12"	18.5"
BPCFES200	61"	13"	19.5"

